## 2°C~8°C Pharmacy Refrigerator



# YC-1505L

### 

The multi-duct vortex refrigeration system and finned evaporator can prevent frosting completely and improve temperature uniformity to a large extent.

### 🔯 Real Energy Saving

The refrigerator is equipped with "M + Energy Core" power management system and complete air cooling design, improving energy saving efficiency by more than 40%.

### Real Visibility

The electrical heating + LOW-E design with double considerations can achieve a better anti-condensation effect for the glass door.

### **Real Safety**

Seven temperature probes can ensure high precision of temperature control with nearly no fluctuation and thus can improve safety.

#### Intelligent Temperature Control

-----

· Equipped with high-precision microcomputer temperature control system and 1 highbrightness digital temperature display with display accuracy at 0.1°C. Equipped with a remote alarm access port and 485 data access port.



#### Security System

- The well-developed audible & visual alarm system with multiple audible & visual alarm functions: high temperature alarm, low temperature alarm, sensor failure alarm, door opening alarm, power outage alarm;
- The turn-on delay and stopping interval protection function can ensure reliability in running:
- The door is equipped with a lock, preventing it from opening accidentally.



#### **Refrigeration System**

Equipped with a compressor supplied by an international famous brand, high-efficiency air-cooled condenser and finned evaporator, ensuring fast refrigeration.

### Scope of Application


Suitable for storage of biological products, vaccines, drugs, reagents, etc. Suitable for use in pharmacies, pharmaceutical factories, hospitals, centers for disease prevention & control, clinics, etc.

### Performance Data / Cooling Curve




from PVC-coated steel wire with tag cards · Upgrade with aluminium alloy door handle, ensuring elegance of appearance;

enience to users in testing temperature inside the cabinet.



🗠 External Dimensions







#### **Data Storage**

· Equipped with a USB export interface, which can be used for exporting data in PDF, The default time range for exporting is from the previous month to the current month ·When a U-disk is connected, temperature data can be stored continuously and automatically (data can be stored for 100,000 sets of data); · The printer is optional.



### Human-oriented

· Equipped with high-quality shelves made and classification marks, which are easy to clean;

Equipped with testing port, bringing conv-

## M Specification Chart

2~8°C Pharmacy Refrigerator	
Model	YC-1505L
Cabinet Type	Upright
Capacity(L)	1505
Internal Size(W*D*H)mm	1685*670*1514
External Size(W*D*H)mm	1798*886*1997
Package Size(W*D*H)mm	1928*988*2165
NW/GW(Kgs)	322/414
Performance	
Temperature Range	2~8°C
Ambient Temperature	16-32°C
Cooling Performance	5℃
Climate Class	Ν
Controller	Microprocessor
Display	Digital display
Refrigeration	
Compressor	lpc
Cooling Method	Air cooling
Defrost Mode	Automatic
Refrigerant	R290
Insulation Thickness(mm)	R/L:55,U:65,D:62,B:55
Construction	
External Material	PCM
Inner Material	Stainless steel
Shelves	18(coated steel wired shelf)
Door Lock with Key	Yes
Lighting	LED
Access Port	1pc. Ø 25 mm
Casters	6 (3 casters with brake)
Data Logging/Interval/Recording Time	USB/Record every 10 minutes / 2 years
Door with Heater	Yes
Alarm	
Temperature	High/Low temperature,High ambient temperature
Electrical	Power failure , Low battery
System	Sensor error,Door ajar, Built-in USB datalogger failure,Condenser overheating
Electrical	
Power Supply(V/HZ)	220/50
Rated Power(W)	620
Rated Current(A)	5.2
Power Consumption(KWh/24h)	11.18
Accessories	
Options	Printer
Standard	RS485, Remote alarm contact, Backup battery
The model, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading.	

\*The model, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading. \*There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.

