

# Vertical emergency eye wash

EEWS-322



## Description

- Combination eye wash stations combine a shower and an eye wash in a single unit.
- The shower provides a full body washdown to prevent injury after being exposed to hazardous materials.
- The eye wash flushes irritants from eyes to treat and prevent eye injuries.
- These stations are used in labs, chemical plants, paper mills, and other environments where there are potentially harmful chemicals or materials. They allow fast emergency access when installed near areas where harmful chemicals or materials are being handled.

## Specifications

Model	EEWS-322
Materials	SS304
Surface finishing	fine polishing
Function	eye and face washing
Switching ball valve	two-piece ball valve
Pipe diameter	48mm/38mm
Nominal pressure	1.0Mpa
Working pressure	0.2-0.4Mpa
Test pressure	1.5Mpa
Working environment temperature	0°C-40°C
Eye wash/face wash water flow	≥11.4 L/min
Flow of eye wash	≥1.5 L/min
Eye wash bowl	300mm straight edge design, gather water, prevent splash
Dust cover	integrated design of main body, not easy to lose
Inner size	G1/2" male
Outlet size	Rp1-1/4" female
Inlet height	780mm/753mm
Outlet height	108mm/86mm
Product features	After the use of eye wash and face wash is stopped, the water in the pipeline will be drained automatically to achieve the purpose of anti-freezing

# Vertical Emergency Eye Wash

EEWS-327



## Description

- After the use of eye wash and face wash is stopped, the water in the pipeline will be drained automatically to achieve the purpose of anti-freezing
- The inlet part and outlet part are customizable
- Shut off valve and filter are proposed to be equipped on the water-supply end
- Stainless steel foot treadle can be added to control the eye wash switch.

## Specifications

Model	EEWS-327
Materials	SS304
Surface finishing	Fine polishing
Function	Eye and face washing
Switching ball valve	Two-piece ball valve
Pipe diameter	48mm/38mm
Nominal pressure	1.0Mpa
Working pressure	0.2-0.4Mpa
Test pressure	1.5Mpa
Working environment temperature	0°C-40°C
Eye wash/face wash water flow	≥11.4 L/min
Flow of eye wash	≥1.5 L/min
Eye wash bowl	300mm straight edge design, gather water, prevent splash
Dust cover	Integrated design of main body, not easy to lose
Inner size	G1/2" male
Outlet size	Rp1-1/4" female
Inlet height	780mm/753mm
Outlet height	108mm/86mm